

for
allowance
use original
claim
numbers
A
P. Hoffer
11/14/02

- 1 1. A motorcycle having a transmission system that accommodates an enlarged rear
- 2 tire, the motorcycle comprising in combination:
- 3 a. a support frame for supporting a rider, the support frame extending along a
- 4 longitudinal axis between opposing front and rear ends;
- 5 b. a rear wheel rotatably coupled to the rear end of the support frame, the rear wheel
- 6 including a rear wheel drive gear for applying torque to the rear wheel, the rear wheel drive
- 7 gear extending substantially in a first vertical plane spaced apart from the longitudinal axis of
- 8 the support frame by a first offset distance;
- 9 c. an engine mounted to the support frame for generating a turning force to propel the
- 10 motorcycle;
- 11 d. a transmission mounted to the support frame and coupled to the engine for
- 12 selectively coupling the turning force generated by the engine to a transmission output gear,
- 13 the transmission output gear extending substantially in a second vertical plane spaced apart
- 14 from the longitudinal axis of the support frame by a second offset distance, the second offset
- 15 distance being smaller than the first offset distance;
- 16 e. an intermediate shaft rotatably secured to the support frame and disposed generally
- 17 between the transmission output gear and the rear wheel drive gear, the intermediate shaft
- 18 including a power input gear, the power input gear extending substantially in said second
- 19 vertical plane and spaced apart from the longitudinal axis of the support frame by said second
- 20 offset distance, said intermediate shaft also including a power output gear that rotates together
- 21 with the power input gear, the power output gear extending substantially in said first vertical
- 22 plane and spaced apart from the longitudinal axis of the support frame by said first offset
- 23 distance;
- 24 f. a first drive belt coupling the transmission output gear to the power input gear of the
- 25 intermediate shaft; and
- 26 g. a second drive belt coupling the power output gear of the intermediate shaft to the
- 27 rear wheel drive gear.

28

A

1 Please add new claims 8-15, as follows:

2
3 8. The motorcycle recited by claim 1 wherein the intermediate shaft is located
4 generally within the support frame.

5
6 9. A motorcycle having a transmission system that accommodates an enlarged rear
7 tire, the motorcycle comprising in combination:

8 a. a support frame for supporting a rider, the support frame extending along a
9 longitudinal axis between opposing front and rear ends;

10 b. a rear wheel rotatably coupled to the rear end of the support frame, the rear wheel
11 including a rear wheel drive gear for applying torque to the rear wheel, the rear wheel drive
12 gear extending substantially in a first vertical plane spaced apart from the longitudinal axis of
13 the support frame by a first offset distance;

14 c. an engine mounted to the support frame for generating a turning force to propel the
15 motorcycle;

16 d. a transmission mounted to the support frame and coupled to the engine for
17 selectively coupling the turning force generated by the engine to a transmission output gear,
18 the transmission output gear extending substantially in a second vertical plane spaced apart
19 from the longitudinal axis of the support frame by a second offset distance, the second offset
20 distance being smaller than the first offset distance; and

21 e. an intermediate shaft located generally within the support frame and rotatably
22 secured to the support frame, the intermediate shaft including a power input gear, the power
23 input gear extending substantially in said second vertical plane and spaced apart from the
24 longitudinal axis of the support frame by said second offset distance, said intermediate shaft
25 also including a power output gear that rotates together with the power input gear, the power
26 output gear extending substantially in said first vertical plane and spaced apart from the
27 longitudinal axis of the support frame by said first offset distance.

28

1 10. The motorcycle recited by claim 9 wherein the intermediate shaft is disposed
2 generally between the transmission output gear and the rear wheel drive gear.

3
4 11. The motorcycle recited by claim 9 wherein the intermediate shaft is disposed
5 generally between the transmission output gear and the rear wheel drive gear, further
6 including:

7 f. a first drive belt coupling the transmission output gear to the power input gear of the
8 intermediate shaft; and

9 g. a second drive belt coupling the power output gear of the intermediate shaft to the
10 rear wheel drive gear.

11
12 12. A motorcycle having a transmission system that accommodates an enlarged rear
13 tire, the motorcycle comprising in combination:

14 a. a support frame for supporting a rider, the support frame extending along a
15 longitudinal axis between opposing front and rear ends, and wherein the support frame
16 includes a tail frame portion for supporting a rear wheel, the tail frame portion being pivotally
17 secured to the support frame about a tail pivot axis, and the rear wheel being rotatably secured
18 to the tail frame portion;

19 b. a rear wheel drive gear for applying torque to the rear wheel, the rear wheel drive
20 gear extending substantially in a first vertical plane spaced apart from the longitudinal axis of
21 the support frame by a first offset distance;

22 c. an engine mounted to the support frame for generating a turning force to propel the
23 motorcycle;

24 d. a transmission mounted to the support frame and coupled to the engine for
25 selectively coupling the turning force generated by the engine to a transmission output gear,
26 the transmission output gear extending substantially in a second vertical plane spaced apart
27 from the longitudinal axis of the support frame by a second offset distance, the second offset
28 distance being smaller than the first offset distance; and